

Tensión de Red	SOFT-STARTER SSW-03			MOTOR MAXIMO APLICABLE <sup>(1)</sup>								Tamaño		
	Modelo	Inominal (A)		Tensión (V)	Conexión Standard (3 cables)				Conexión opcional (6 cables)					
		40°C	55°C		Ta=0...40°C <sup>(2)</sup>		Ta=40...55°C <sup>(2)</sup>		Ta=0...40°C <sup>(2)</sup>		Ta=40...55°C <sup>(2)</sup>			
					HP	kW	HP	kW	HP	kW	HP		kW	
<b>220 / 230 / 240 / 380 / 400 / 415 / 440 V</b>	120/220-440	120	100	220	75	37	40	30	75	55	75	55	0	
	170/220-440	170	145		50	55	50	37	125	90	100	75	90	1
	205/220-440	205	170		85	63	75	55	150	110	125	90	125	2
	255/220-440	255	255		100	75	100	75	175	130	175	130	175	3
	290/220-440	290	290		125	90	125	90	200	150	200	150	200	4
	340/220-440	340	290		140	103	125	90	250	185	200	150	250	5
	410/220-440	410	380		150	110	150	110	300	220	250	185	300	6
	475/220-440	475	475		200	150	200	150	350	260	330	240	350	7
	580/220-440	580	500		250	185	200	150	400	300	350	260	400	8
	670/220-440	670	550		270	200	225	166	450	300	400	300	450	9
	800/220-440	800	620		300	220	250	185	550	400	450	330	550	10
	950/220-440	950	800		400	300	300	220	650	475	550	400	650	11
	1100/220-440	1100	850		450	330	350	260	800	600	600	450	800	12
	1400/220-440	1400	1080		600	450	450	330	1000	750	730	550	1000	13
	120/220-440	120	100		75	55	75	55	150	110	125	90	150	14
	170/220-440	170	145	125	90	100	75	200	150	175	130	200	15	
	205/220-440	205	170	150	110	125	90	250	185	200	150	250	16	
	255/220-440	255	255	175	130	175	130	300	220	300	220	300	17	
	290/220-440	290	290	200	150	200	150	350	260	350	260	350	18	
	340/220-440	340	290	250	185	200	150	400	300	350	150	400	19	
	410/220-440	410	380	300	220	270	200	500	370	450	330	500	20	
	475/220-440	475	475	350	260	350	260	600	450	600	450	600	21	
	580/220-440	580	500	400	300	370	270	700	500	630	470	700	22	
	670/220-440	670	550	500	330	400	300	850	630	700	500	850	23	
	800/220-440	800	620	550	400	450	330	1000	730	750	550	1000	24	
	950/220-440	950	800	700	550	600	450	1200	900	1000	730	1200	25	
	1100/220-440	1100	850	850	600	650	475	1350	1000	1050	770	1350	26	
1400/220-440	1400	1080	1050	730	800	600	1750	1300	1350	1000	1750	27		
<b>460 / 480 / 575 V</b>	120/460-575	120	100	440	100	75	75	55	175	130	150	110	0	
	170/460-575	170	145		125	110	100	75	250	185	200	150	250	1
	205/460-575	205	170		150	125	125	90	300	220	250	185	300	2
	255/460-575	255	255		200	150	200	150	350	260	350	260	350	3
	290/460-575	290	290		250	185	250	185	400	300	400	300	400	4
	340/460-575	340	290		300	200	250	185	500	370	400	300	500	5
	410/460-575	410	380		350	260	300	220	600	450	550	400	600	6
	475/460-575	475	475		400	300	400	300	700	500	650	475	700	7
	580/460-575	580	500		500	370	430	315	850	630	700	500	850	8
	670/460-575	670	550		550	400	450	330	950	700	800	600	950	9
	800/460-575	800	620		700	500	500	370	1150	850	900	660	1150	10
	950/460-575	950	800		800	600	700	500	1400	1050	1150	850	1400	11
	1100/460-575	1100	850		950	660	750	550	1600	1200	1250	920	1600	12
	1400/460-575	1400	1080		1200	900	900	660	2050	1500	1550	1150	2050	13
	120/460-575	120	100		125	90	100	75	225	165	175	130	225	14
	170/460-575	170	145	150	110	150	110	300	220	270	200	300	15	
	205/460-575	205	170	220	160	175	130	400	300	300	220	400	16	
	255/460-575	255	255	250	185	250	185	450	330	450	330	450	17	
	290/460-575	290	290	300	220	300	220	550	400	550	400	550	18	
	340/460-575	340	290	350	250	300	220	650	475	550	400	650	19	
	410/460-575	410	380	450	330	400	300	750	550	700	500	750	20	
	475/460-575	475	475	500	370	500	370	900	660	900	660	900	21	
	580/460-575	580	500	600	450	550	400	1100	800	950	700	1100	22	
	670/460-575	670	550	750	550	600	450	1250	920	1050	770	1250	23	
	800/460-575	800	620	850	660	700	500	1500	1100	1150	850	1500	24	
	950/460-575	950	800	1050	800	850	630	1800	1300	1500	1100	1800	25	
	1100/460-575	1100	850	1200	900	950	700	2100	1550	1600	1200	2100	26	
1400/460-575	1400	1080	1500	1100	1200	900	2650	1950	2050	1500	2650	27		