

Tensión de la Red	SOFT-STARTER SSW-06		MOTOR MÁXIMO APLICABLE				Mecánica	
	Modelo (tensión de comando: 90-250 Vca)	Inominal (A) Ta=0...50°C	Tensión (V)	Conexión Estándar (3 cables)		Conexión Dentro del Delta del Motor (6 cables)		
				Ta=0...50°C		Ta=0...50°C		
				cv	kW	cv		kW
220/230/240/380/400/415/440/460/480/575 V	0085 T 2257 P S	85	220	30	22	60	45	2
	0130 T 2257 P S	130		50	37	75	55	2
	0170 T 2257 P S	170		60	45	125	90	3
	0205 T 2257 P S	205		75	55	150	110	3
	0255 T 2257 P S	255		100	75	175	130	4
	0312 T 2257 P S	312		125	90	200	150	4
	0365 T 2257 P S	365		150	110	250	185	4
	0085 T 2257 P S	85		60	45	100	75	2
	0130 T 2257 P S	130		75	55	150	110	2
	0170 T 2257 P S	170		125	90	200	150	3
	0205 T 2257 P S	205		150	110	250	185	3
	0255 T 2257 P S	255		175	130	300	220	4
	0312 T 2257 P S	312	200	150	350	260	4	
	0365 T 2257 P S	365	250	185	450	330	4	
	0085 T 2257 P S	85	60	45	125	90	2	
	0130 T 2257 P S	130	100	75	175	130	2	
	0170 T 2257 P S	170	125	90	200	150	3	
	0205 T 2257 P S	205	150	110	300	220	3	
	0255 T 2257 P S	255	200	150	350	260	4	
	0312 T 2257 P S	312	250	185	450	330	4	
	0365 T 2257 P S	365	300	220	500	370	4	
	0085 T 2257 P S	85	75	55	150	110	2	
	0130 T 2257 P S	130	90	90	200	150	2	
	0170 T 2257 P S	170	130	130	300	220	3	
0205 T 2257 P S	205	150	150	350	260	3		
0255 T 2257 P S	255	185	185	450	330	4		
0312 T 2257 P S	312	220	220	550	400	4		
0365 T 2257 P S	365	300	300	650	475	4		


MEC 02

MEC 03

MEC 04